

RM51

miniature relays



- DC coils - of up to 48 V DC, insulation class F: 155 °C
- For PCB
- Small dimensions
- High switching capacity
- Applications: for household electrical appliance, automation systems, electronic equipment, instrument and meter, telecommunication devices, remote control facilities
- Recognitions, certifications, directives: RoHS, 

Contact data

Number and type of contacts		1 CO, 1 NO
Contact material		AgSnO₂
Rated / max. switching voltage	AC	250 V / 277 V
Min. switching voltage		5 V
Rated load	AC1	1 CO: 10 A / 7 A (NO/NC) / 250 V AC 1 CO: 20 A / 20 A (NO/NC) / 125 V AC
	DC1	1 CO: 10 A / 7 A (NO/NC) / 30 V DC 1 NO: 10 A / 250 V AC 1 NO: 20 A / 125 V AC 1 NO: 10 A / 30 V DC
Motor load	acc. to UL 508	1 CO: 1 HP / 1/2 HP 1 NO: 1 HP
	AC3 acc. to IEC 60947-4-1	250 V AC, (NO/NC), single-phase motor 250 V AC, single-phase motor 1 CO: 0,75 kW / 0,375 kW 1 NO: 0,75 kW 250 V AC, (NO/NC), single-phase motor 250 V AC, single-phase motor
Min. switching current		15 mA
Rated current		10 A
Max. breaking capacity	AC1	3 000 VA
Contact resistance		≤ 100 mΩ

Coil data

Rated voltage	DC	5, 9, 12, 24, 48 V
Must release voltage		DC: ≥ 0,05 U _n
Operating range of supply voltage		see Table 1
Rated power consumption	DC	0,36 W

Insulation according to EN 60664-1

Rated surge voltage		4 000 V	1,2 / 50 μs
Insulation resistance		250 MΩ	500 V DC, 60 s
Dielectric strength			
• between coil and contacts		2 500 V AC	type of insulation: basic
• contact clearance		1 000 V AC	type of clearance: micro-disconnection
Contact - coil distance			
• clearance		≥ 1,9 mm	
• creepage		≥ 1,9 mm	

General data


Operating / release time (typical values)		15 ms / 10 ms
Electrical life (number of cycles)		
• resistive AC1	360 cycles/hour	10 ⁵ 1 CO: 10 A / 7 A (NO/NC), 250 V AC
• resistive DC1	360 cycles/hour	10 ⁵ 1 CO: 10 A / 7 A (NO/NC), 30 V DC
Mechanical life	18 000 cycles/hour	10 ⁷ 1 NO: 10 A, 250 V AC 1 NO: 10 A, 30 V DC
Dimensions (L x W x H)		19,5 x 16 x 17,1 mm
Weight		10 g
Ambient temperature		
(non-condensation and/or icing)	• operating	-40...+85 °C
Cover protection category		IP 67 EN 60529
Environmental protection		RTIII EN 61810-1
Shock resistance		10 g
Vibration resistance		1,0 mm DA (constant amplitude) 10...55 Hz
Solder bath temperature		max. 260 °C
Soldering time		max. 5 s

The data in bold type relate to the standard versions of the relays.


RM51

miniature relays


Dimensions



Connection diagrams (pin side view)



Pinout (solder side view)



Mounting


Relays **RM51** are designed for direct PCB mounting.

Coil data - DC voltage version

Table 1

Coil code	Rated voltage V DC	Coil resistance at 20 °C Ω	Acceptable resistance	Coil operating range V DC	
				min. (at 20 °C)	max. (at 20 °C)
1005	5	69	$\pm 10\%$	3,75	6,5
1009	9	225	$\pm 10\%$	6,75	11,7
1012	12	400	$\pm 10\%$	9,00	15,6
1024	24	1 600	$\pm 10\%$	18,00	31,2
1048	48	6 400	$\pm 10\%$	36,00	62,4

Ordering codes



Examples of ordering codes:

- RM51-3011-85-1012** relay **RM51**, for PCB, one changeover contact, contact material AgSnO₂, coil voltage 12 V DC, in cover IP 67
- RM51-3021-85-1048** relay **RM51**, for PCB, one normally open contact, contact material AgSnO₂, coil voltage 48 V DC, in cover IP 67

PRECAUTIONS:

1. Ensure that the parameters of the product described in its specification provide a safety margin for the appropriate operation of the device or system and never use the product in circumstances which exceed the parameters of the product. 2. Never touch any live parts of the device. 3. Ensure that the product has been connected correctly. An incorrect connection may cause malfunction, excessive heating or risk of fire. 4. In case of any risk of any serious material loss or death or injuries of humans or animals, the devices or systems shall be designed so to equip them with double safety system to guarantee their reliable operation.